




LEI proprietary LED BLUE

WDL Series

Tube is not colored.
Special LED proprietary Blue



Blue for illustration purposes only. Color deep dark blue, which simulates Black light color

Date	Catalog #
Type	Project
Prepared by	Comments

Features and Specifications

ENCLOSURE

High impact, .125" DR blended acrylic FROSTED tube sealed with custom molded gaskets and stainless steel endcaps. A proprietary two point closure system ensures a positive seal. All exposed hardware is stainless steel.

INTERIOR HOUSING

Extruded aluminum gear tray with integrated LED mounting rails and proprietary stainless steel double studs. Driver(s) enclosed by a heat dissipating aluminum cover.

ELECTRICAL

Universal voltage (120V-277V), constant current Class 2 driver. High quality, mid-power LED boards rated at 50,000 hours. Standard fixture supplied with 3-wire, yellow, six-foot, #16 AWG, STOW cable secured by a proprietary, stainless steel, potted strain relief.

MOUNTING

Three stainless steel options available:

- Adjustable Wire Hanger Mount
- Proprietary Adjustable / Fixed Mount
- Proprietary Band Mount

CERTIFICATIONS

- ETL listed UL 1598 for Wet Location
- ETL listed UL 1598 for Battery Back-Up
- ETL listed CSA Std. C22.2 No. 250.0
- ETL listed ANSI/NSF 2 for Splash Zones
- IP69K rated

Description

The **WDL Blue LED Series** is the latest proprietary fixture in the LEI line of washdown products. The energy efficient linear LED fixture designed specifically for the concept of quelling poultry. The **WDL Blue LED Series** replaces outdated UV Black light bulbs, which could have harmful UV range.


Many companies sell a "Blacklight LED version" or a "Blue" in color LED adapted from a carwash, for this purpose. LEI has taken it a step further with a specific range, that is outside the UV zone in an attempt to emulate the calming effect.

The WDL utilizes a proprietary two point closure system comprised of stainless steel end caps and custom molded gaskets to ensure a positive seal. The component base design allows for quick and easy maintenance. The IP69K rated enclosure utilizes a robust .125" thick chemical and impact resistant **FROSTED** lens to provide a **GLARE FREE**, wide distribution light pattern.

The "LM" standard 4 ft unit only utilizes 14 watts.



Dimensions



Warranty

- 5-year limited warranty. (See LEI's LED Warranty for complete details.)
- Optional Internal Blue Filter is not covered by standard warranty and could require change approximately every 2 years depending on usage. Filter replacement shipped free during that period.

Ordering Information

Example Catalog Number – W8-BL-Special-U-LM-BF

W	8	BL	Special	U	LM	BF
A	B	C	D	E	F	G
Series	Length	Color	CCT	Voltage	Output	Options & Power End
		Output	CRI			

Catalog Logic:

A. Series

W = WDL

B. Length

4 = 4'
8 = 8'

C. Color

BL = LED BLUE

D. CCT and CRI

Special = Proprietary Blue LED configuration.

E. Voltage

U = (120V-277V)
UNB = (120V-277V) Non-Switching Battery Back-Up
USB = (120V-277V) Switching Battery Back-Up

F. Output

LM = Low Medium Energy minded

G. Options

BF = Darker Blue transmission
Proprietary LEI color Filter.

H. Optional Power End

All fixtures come standard with 6' Yellow Lead, 3-wire, 16 AWG. Or select from the options below.


R3 = Mini-Receptacle, 3-wire, Male

Below - 4 wire for switching scenarios.
R4 = Mini-Receptacle, 4-wire, Male
4P6 = 6' Yellow Lead, 4-wire, 16 AWG

Replacement Parts & Accessories

SF3-6	Mini-Connector, 3-wire, Female – 6'
SF4-6	Mini-Connector, 4-wire, Female – 6' Frosted
WFT-4	Tube Lens – 4'
WFT-8	Frosted Tube Lens – 8'
W-ECK	Stainless Steel Non-Electrical End Cap Kit
W-ECKE	Stainless Steel Electrical End Cap Kit
W-AFK	Stainless Steel Adjustable/Fixed Mounting Kit
W-BMK	Stainless Steel Band Mounting Kit

Mounting Options



Performance Data

Catalog Number	Length	Lumen Output	CCT	Actual Lumens	System Watts
W4-BL-Special-U-LM	4'	Low Medium	BLUE	N/A	14
W8-BL-Special-U-LM	8'	Low Medium		N/A	28

Numbers in italics are calculated using LED manufacturers' data.

