



WDL-U_P light Series





Description

The **WDL-U Series** features **Uplight and Downlight** in an energy efficient linear LED fixture designed specifically for heavy hose-down applications. The **WDL-UPLIGHT** features a 60/40 ratio of downlight to uplight to maintain your task lighting needs. Independent LED Drivers for the Uplight and the Downlight, providing autonomous operation. The **WDL-U Series** utilizes a proprietary two point closure system comprised of stainless steel end caps and custom molded gaskets to ensure a positive seal. The component based design allows for quick and easy maintenance. The IP69K rated enclosure utilizes a robust .125" thick chemical and impact resistant **FROSTED** lens to provide a **GLARE FREE**, wide distribution light pattern similar to fluorescent products.

ETL Listed UL1598 for Wet Location, Battery Back-Up, CSA Std. C22.2 No. 250.0, ANSI/NSF 2 for Splash Zones, and IP69K rated; the **WDL-U Series** is designed to hold up to daily sanitation while meeting all USDA requirements.

Dimensions



Date	Catalog #
Type	Project
Prepared by	Comments

Features and Specifications

ENCLOSURE

High impact, .125" DR blended acrylic FROSTED tube sealed with custom molded gaskets and stainless steel endcaps. A proprietary two point closure system ensures a positive seal. All exposed hardware is stainless steel.

INTERIOR HOUSING

Extruded aluminum gear tray with integrated LED mounting rails and proprietary stainless steel double studs. Driver(s) enclosed by a heat dissipating aluminum cover.

ELECTRICAL

Universal voltage (120V-277V), constant current Class 2 driver. High quality, mid-power LED boards rated at 50,000 hours. Standard fixture supplied with 3-wire, yellow, six-foot, #16 AWG, STOW cable secured by a proprietary, stainless steel, potted strain relief.


MOUNTING

Three stainless steel options available:

- Adjustable Wire Hanger Mount
- Proprietary Adjustable / Fixed Mount
- Proprietary Band Mount

Distribution

Unique Uplight distribution pattern allows for more even lighting pattern throughout the working area, with the focus remaining on the work plane.



CERTIFICATIONS

- ETL listed UL 1598 for Wet Location
- ETL listed UL 1598 for Battery Back-Up
- ETL listed CSA Std. C22.2 No. 250.0
- ETL listed ANSI/NSF 2 for Splash Zones
- IP69K rated

Warranty

- 3-year limited warranty.
(See LEI's LED Warranty for complete details.)

Ordering Information

Example Catalog Number – WU4-H45-85-U

WU	4	-	H	45-85	-	U	-		-	
A	B		C	D		E		F		G
Series	Length		Lumen	CCT and CRI		Voltage		Optional Power End		Optional Controls

Catalog Logic:

A. Series

WU = WDL Uplight

B. Length

4 = 4'
8 = 8' (Pending)

C. Lumen Output

H = High

D. CCT and CRI

45-85 = 4500K, 85 CRI

E. Voltage

U = (120V-277V)
UNB = (120V-277V) Non-Switching Battery Back-Up*
USB = (120V-277V) Switching Battery Back-Up*

F. Optional Power End

All fixtures come standard with 6' Yellow Lead, 3-wire, 16 AWG. Or select from the options below.

R3 = Mini-Receptacle, 3-wire, Male
R4 = Mini-Receptacle, 4-wire, Male
4P6 = 6' Yellow Lead, 4-wire, 16 AWG

G. Optional Controls

MOS = Wet Location Motion Sensor**
DMS = Dimming Motion Sensor -Wet**

*Battery Back-up models are limited to 30 C ambient temperatures
**Motion sensing may be limited based on the configuration you order.

Performance Data

Catalog Number	Length	Lumen Output	CCT	Distribution Lumens	System Watts	Lumens per Watt	CRI
WU4-H45-85-U	4'	9194	4500K	UP 3,727	72	127	85
				DOWN 5,467			


Numbers in italics are calculated using LED manufacturers' data.

Consult factory for all available options & configurations.


Replacement Parts & Accessories

SF3-6	Mini-Connector, 3-wire, Female – 6'
SF4-6	Mini-Connector, 4-wire, Female – 6' Frosted
WFT-4	Tube Lens – 4'
WFT-8	Frosted Tube Lens – 8'
W-ECK	Stainless Steel Non-Electrical End Cap Kit
W-ECKE	Stainless Steel Electrical End Cap Kit Stainless
W-AFK	Steel Adjustable/Fixed Mounting Kit Stainless
W-BMK	Steel Band Mounting Kit


Mounting Options



W-WHK
(Comes standard with fixture)



W-AFK



W-BMK

