

OPT



- * DLC Listed
- * IP69K Rated
- * ETL Listed UL 1598 for Wet Locations
- * ETL Listed UL 1598 for Battery Back-Up
- * ETL Listed CSA Std. C22.2 No. 250.0
- * ETL Listed ANSI/NSF 2 for Splash Zones
- * 40°C Rated
- * 4 Lumen Packages
- * 4000K or 5000K CCT
- * Nichia >80 CRI LEDs
- * 3yr and 5yr Warranty Options



LIGHTING
ETC. INCORPORATED

PRODUCT OVERVIEW

The OPT Series is the new, compact, lightweight, wet location, energy efficient, LED Alternative to 250-400 watt metal halide fixtures. It is maintenance-friendly and fully accessible, while the smooth water-shed design allows for superior clean-up during sanitation. The OPT Series is the OPTIMUM general lighting solution for the food and beverage industry, or any harsh or hose-down environment.

PRODUCT FEATURES

HEAVY DUTY, 2-PIECE, ALL ALUMINUM HOUSING WITH WATER-SHED DESIGN:

Designed for superior thermal management and ease of maintenance. Allows for easy clean-up during sanitation. No exposed heat sinks, fins or openings.

THREADED TOP HUB AND SAFETY CABLE EYELET:

No penetration in 3/4" hub to prevent water ingress and eyelet allows for use of optional SS safety cable.

IP RATED LED DRIVERS AND HIGH PERFORMANCE LEDs:

Available in (120V-277V), 480V. Battery Back-Up offered in most models. Battery Back-Up models include RED top cap for easy identification. Includes custom, metal-clad boards with Nichia >80 CRI LEDs.

STAINLESS STEEL, CAPTIVE, EXTERNAL HARDWARE:

Fixture is fully accessible with only 14 captive SS fasteners.



BOTTOM VIEW, SHOWN WITH OPTIONAL DOMED LENS.

LOW GLARE ACRYLIC LENS:

Flat, low glare, acrylic lens standard with optional domed lens available.

STAINLESS STEEL RETAINER RING:

Lens is sealed in place with SS retainer ring and captive SS fasteners.

OPTIONAL LIGHTING CONTROLS:

Optional internal occupancy sensor allows for multi-level lighting control.

MOUNTING OPTIONS

SS MOUNTING HOOK INCLUDED:

LEI Stainless Steel Mounting hook is included or utilize 3/4" NPT pendant mounting hub.

OPTIONAL SS SAFETY CABLE:

Stainless steel safety cable available in 5' and 10' lengths.



SHOWN WITH SS MOUNTING HOOK AND SAFETY CABLE.

